

TECHNICAL DATA SHEET

PA413 - PERFILADOR

1. IDENTIFICATION OF THE PREPARATION AND COMPANY

PINTURAS SERRANO 2011, S.L.

Pol. Ind. El Salvador

Avda. Segunda Parcela 81

02630 La Roda (Albacete)

Phone number: +34 967443657 Tel and fax +34 967441351

Email: info@resitop.com

Preparation name: **PERFILADOR**

Code: PA413

Use of the preparation: RESITOP surface signage.

2. DEFINITION

Transparent paint that is applied as a sealing layer of the marking tape prior to applying Pintaline signage paint. The product admits an amount of silica aggregate of 0.2 mm in order to recreate a non-slip micro-texture on the surface.

3. FIELDS OF APPLICATION

Marking for sports courts made with RESITOP systems.

Lettering on work surfaces.

4. SURFACE PREPARATION

The surface must be clean, dry and stain free.

On surfaces that have already been painted, remove the remains of badly-adhered old paints.

5. APLICATION

Tape the lines to be painted on both sides and apply a layer of PERFILADOR in order to seal the tape and avoid any possibility that the Pintaline colour paint can run under the tape, thus avoiding any imperfection.

Once the product has been applied, the utensils and tools used should be cleaned with water.

6. TECHNICAL CHARACTERISTICS

- Nature:** Acrylic dispersion.
Aspect: Smooth, satin.
Colour: Transparent
Yield: 150 gr/m²
Drying: To the touch, 1 to 2 hours (25°C) depending on prevailing wind and humidity.
Curing: 15 days (total drying for maximum yield).
Odour: Weak characteristic smell.

7. PRECAUTIONS

- Always use clean drinking water.
Do not apply at temperatures below 10°C.
Do not use if imminent rain is forecast.
Store the product protected from possible frost or exposure to the sun.
The maximum recommended storage is 12 months from its manufacture date in its original unopened container.
For its preservation it is advisable not to add water to the material that will not be used.

8. HYGIENE AND SAFETY

- Do not eat, drink or smoke during use.
Keep out of the reach of children.
Avoid contact with skin and eyes.
Store the product in dry areas, and at a temperature between 5°C and 35°C.
Do not pour the waste down the drain.
Comply with prevailing Health and Safety at work legislation.
The person responsible for delivering the container waste or used container, for its proper environmental management, will be its final owner.
For more information see safety data sheet.

9. NOTES

The data reviewed here are based on our current knowledge, laboratory tests and practical use in specific circumstances and through objective judgements.

This data sheet overrides and replaces any previous one related to the same product.

MANUFACTURED IN SPAIN.

MANUFACTURED IN THE EU