

# **TECHNICAL DATA SHEET**

## **PA409 - PINTA LINE**

### **1. IDENTIFICATION OF THE PREPARATION AND COMPANY**

**PINTURAS SERRANO 2011, S.L.**

Pol. Ind. El Salvador

Avda. Segunda Parcela 81

02630 La Roda (Albacete)

Phone number: +34 967443657 Tel and fax +34 967441351

Email: [info@resitop.com](mailto:info@resitop.com)

Preparation name: **PINTA LINE**

Code: PA409

Use of the preparation: RESITOP surface signage. Acrylic satin plastic.

### **2. DEFINITION**

Marking paint for sports courts made with RESITOP systems. Formulated from pure, highly-pigmented acrylic resins, in order to provide this signaling with good anchoring, high-wear resistance and high sunlight resistance.

### **3. FIELDS OF APPLICATION**

Marking for sports courts made with RESITOP systems.

Coating or decorating work surfaces (plaster, cement, fibre cement, etc.).

Lettering on work surfaces.

### **4. SURFACE PREPARATION**

The surface must be clean, dry and free of stains.

On already painted surfaces remove the remains of badly adhered old paints.

## **5. APPLICATION**

For track marking, mark these first. Tape the lines to be painted on both sides. Dilute the product for a first coat between 10 - 15% with drinking water, let it dry for 1 - 2 hours (depending on temperature and prevailing humidity) and apply a second coat. For the second coat dilute the product between 5-10% with drinking water.

Using the RESITOP PROFILER lines before painting is recommended. This avoids the paint running under the tape, and thus achieves a completely straight line.

Remove the tape with the wet product, to avoid chipping.

Once the product has been applied, the utensils and tools used should be cleaned with water.

## **6. TECHNICAL CHARACTERISTICS**

- Nature:** Acrylic dispersion.  
**Aspect:** Smooth, satin.  
**Colour:** White, black, ochre, sienna, brown, shadow, yellow, orange, violet, grass green, grey, red, tennis red, dark blue, light blue. (See colour chart).  
**Yield:** 300gr/m<sup>2</sup> (two coats).  
**Drying:** to the touch, 1 to 2 hour (25°C) depending on prevailing wind and humidity.  
**Curing:** 15 days (total drying for maximum yield).  
**Odour:** Weak characteristic smell.

## **7. PRECAUTIONS**

Always use clean drinking water.

Do not apply at temperatures below 10°C.

Do not use if imminent rain is forecast.

Store the product protected from possible frost or exposure to the sun.

The maximum recommended storage is 12 months from its manufacture date in its original unopened container.

For its preservation it is advisable not to add water to the material that will not be used.

## **8. HYGIENE AND SAFETY**

Do not eat, drink or smoke during use.

Keep out of the reach of children.

Avoid contact with skin and eyes.

Store the product in dry areas, and at a temperature between 5°C and 35°C.

Do not pour the waste down the drain.

Comply with prevailing Health and Safety at work legislation.

The person responsible for delivering the container waste or used container, for its proper environmental management, will be its final owner.

For more information see safety data sheet.

## **9. NOTES**

The data reviewed here are based on our current knowledge, laboratory tests and practical use in specific circumstances and through objective judgements.

This data sheet overrides and replaces any previous one related to the same product.

**MANUFACTURED IN SPAIN.**

**MANUFACTURED IN THE EU**

Manufacture and distribution of water-based  
paints, acrylic resins and fillers

