

# **TECHNICAL DATA SHEET**

## **CRACK FILLER**

### **1. IDENTIFICATION OF THE PREPARATION AND COMPANY**

**PINTURAS SERRANO 2011, S.L.**

Pol. Ind. El Salvador

Avda. Segunda Parcela 81

02630 La Roda (Albacete)

Phone number: +34 967443657 Tel and fax +34 967441351

Email: [info@resitop.com](mailto:info@resitop.com)

Preparation name: **CRACK FILLER**

Code: PA401

Use of the preparation: Repairing cracks and hollows.

### **2. DEFINITION**

Crack Filler is a mortar produced based on acrylic resins, ready for use. Studied to correct, fill or repair, minor surface imperfections, such as small hollows, fissures or cracks. It is not valid to repair structural cracks.

### **3. FIELDS OF APPLICATION**

Repair of surface imperfections, in concrete, asphalt, painted surfaces, etc.  
Especially suitable for repairing surfaces made with RESITOP acrylic resin systems.

### **4. SURFACE PREPARATION**

The surfaces to be repaired must be completely clean, dry and free of foreign materials that may prevent good adhesion of the product. Cracks should be cleaned by brush in combination with air or high pressure water jet. Hollows with accumulated dirt should be cleaned with detergent and then rinsed with water. Vegetation should be removed and treated with herbicide before applying Crack Filler.

## **5. APPLICATION**

CRACK FILLER is presented ready for use by spatula or trowel. Designed to correct hollows or cracks not exceeding 5mm, being installed in layers not exceeding 3mm. In the case that two layers had to be applied, the first one would be allowed to dry before applying the second one. It is also advisable to sand down and sweep away any imperfections that may have occurred when applying the mixture. Once the product has been applied, the utensils and tools used should be cleaned with water.

## **6. TECHNICAL CHARACTERISTICS**

<b>Nature:</b>	Acrylic mortar.
<b>Aspect:</b>	Micro-rough.
<b>Colour:</b>	Light beige.
<b>Yield:</b>	1 kg/m <sup>2</sup> approximately per 3mm layer.
<b>Drying:</b>	1 to 2 hours (25°C) depending on prevailing wind and humidity.
<b>Cured:</b>	15 days (total drying)
<b>Odour:</b>	Weak characteristic smell.

## **7. PRECAUTIONS**

Always use clean drinking water.  
Do not apply at temperatures below 10°C.  
Do not use if imminent rain is forecast.  
Store the product protected from possible frost or exposure to the sun.  
The maximum recommended storage is 12 months from its manufacture date in its original unopened container.  
For its preservation it is advisable not to add water to the material that will not be used.

## **8. HYGIENE AND SAFETY**

Do not eat, drink or smoke during use.  
Keep out of the reach of children.  
Avoid contact with skin and eyes.  
Store the product in dry areas, and at a temperature between 5°C and 35°C.  
Do not pour the waste down the drain.  
Comply with prevailing Health and Safety at work legislation.  
The person responsible for delivering the container waste or used container, for its proper environmental management, will be its final owner.  
For more information see safety data sheet.

## **9. NOTES**

The data reviewed here are based on our current knowledge, laboratory tests and practical use in specific circumstances and through objective judgements.

This data sheet overrides and replaces any previous one related to the same product.

**MANUFACTURED IN SPAIN.  
EU**

**MANUFACTURED IN THE**