

PRODUCT TECHNICAL DATA

PA403 - TOPSEAL

1. PRODUCER AND PRODUCT IDENTIFICATION

PINTURAS SERRANO 2011, S.L.

Pol. Ind. El Salvador
Avda, Segunda, Parcela 81
02630 La Roda (Albacete) Spain
Tel. 967443657 Tel y fax 967441351

Product name: **TOPSEAL**

Code : PA403

Filler course underlaymet

2. DESCRIPTION

Topseal is an acrylic emulsion and silica sand slurry, developed specifically to provide a sealed and smooth surface on all properly prepared asphalt surfaces.

3. USES

Topseal may be utilized on all recreational sport asphalt surfacing properly prepared.

4. SURFACE PREPARATION

All surface areas are to be cleansed and repaired prior the application of Topseal. New or existing asphalt courts shall have all cracks and surfaces depressions, greater than 3mm repaired utilizing Crack Filler and Patch Binder in accordance with their respective Product Technical Data.

5. APPLICATION

Topseal must to be job site mixed with water adding from 5 to 10 % of clean water. Apply using a rubber squeegee and always maintaining a wet edge. Successive courses are to be applied only after the previous application has been cured and scraped for imperfections and blow clean.



Manufacture and distribution of painting
to the water, acrylic resins and putties

6. DRYING TIME

One hour to two hour under optimum outdoor drying conditions. For indoor applications fresh air circulation will expedite drying.

7. COVERAGE

Coverage will vary between 1, 5 to 2, 0 kg / m² of undiluted material. Coverage is dependent on such factors as water quantity, surface porosity, climatic conditions, and the technique and expertise of applicator.

8. AVAILABILITY

Topseal is available in black, red, blue and green colour and packaged in 30 kg pail.

9. LIMITATIONS

Use clean potable water in all mixes.

Apply only to properly cured and prepared surfaces.

Do not store in direct sunlight and protect materials from freezing.



Manufacture and distribution of painting
to the water, acrylic resins and putties